

8/16-Port Short Depth PS/2-USB VGA Single Rail WideScreen LCD KVM Switch

CL3108 (CL3108NX: 18.5" LCD)

CL3116 (CL3116NX: 18.5" LCD)

- The ATEN CL3108/CL3116 LCD KVM Switch offers a space-saving, streamlined approach to KVM switch technology by integrating a keyboard, 18.5" LED-backlit LCD monitor, and a touchpad in a 1U rack-mountable sliding housing. The short-depth design maximizes space utility for equipping rack-mounting devices in narrow spaces. In addition, its exclusive LED illumination light provides users with proper visibility when working in low-light conditions.

The CL3108/CL3116 can control up to 8/16 computers; when 8/16 additional KVM switches are cascaded, a single CL3108/CL3116 LCD KVM Switch can control up to 128/256 computers. To achieve greater operational efficiency, the CL3108/CL3116 offers Broadcast mode, which the console spreads out the commands to all computers to perform operations simultaneously. Besides, the Auto scan mode fulfills the needs for continuous monitoring a specific group of computers, and establishing a reliable working environment for users.


To enhance information safety, the CL3108/CL3116 provides two-level password security which restricts unauthorized users from viewing and controlling the computers. For added convenience, the CL3108/CL3116 comes with an additional hot-pluggable USB mouse port that only supports HID device for keyboard and mouse.

As a feature-rich LCD KVM Switch, the CL3108/CL3116 is aimed not just to achieve but exceed the requirements for space utility optimization, superior video quality, adaptive deployment, and operational versatility, and thus is ideal for control rooms with limited space in any industry.

CL3116 Front view



CL3116 Rear view



CL3108 Rear view



Features

Space Utility Optimization

- Exclusive LED illumination light – designed by ATEN to illuminate the keyboard and touchpad to allow visibility in low-light conditions
- Integrated LCD KVM console with an 18.5" LED-backlit widescreen LCD monitor in a single rail housing with top and bottom clearance for smooth operation in a 1U high system rack
- Short-depth design allows you to work with your rack-mounting equipment in narrow spaces
- Console lock – enables the console drawer to remain securely locked away in position when not in use


Reliability and Operational Versatility

- Superior video quality – up to 1366 x 768 @60Hz; DDC2B
- Cascade up to 2 levels – CL3108 controls up to 128 computers or CL3116 controls up to 256 computers from a single console (With compatible KVM Switches: CS1308, CS1316)
- Dual Interface – supports computers with PS/2 or USB keyboards and mice
- Auto PS/2 and USB interface detection
- Keyboard and mouse emulation (PS/2 and USB) for smooth switching and simultaneously booting multiple computers even when the console focus is elsewhere
- Computer selection via pushbuttons, hotkeys, and multilingual on-screen display (OSD)
- Broadcast mode – allows you to send commands from the console to all computers to perform operations simultaneously
- Two level password security – only authorized users can view and control computers
- Auto Scan mode – enables continuous monitoring of user-selected computers
- Keyboard Language supports: English (UK), English (US), German (GER.), German (SWISS.), French, Hungarian, Italian, Japanese, Korean, Russian, Spanish, Swedish and Traditional Chinese
- Additional hot-pluggable USB mouse port on front panel that supports HID device for keyboard and mouse

Installation Flexibility

- Standard rack mount kit included
- Optional Easy Installation Rack Mounting Kit available*
- No software required
- Firmware upgradable
- Supports hot-plugging

*The Easy Installation Rack Mounting Kit is sold separately. Contact your ATEN dealer for product information.



Optional

Rack Mount Kit

Slideaway™ LCD KVM switches/consoles allow you to choose from a host of optional rack mount kits to meet your needs, including the Single Person Easy Installation Rack Mount Kit, which streamlines the rack mounting process.

Normal rack mounting procedures call for at least two people to rack mount a KVM switch/console. The Single Person Easy Installation Rack Mount Kit enables one person to rack mount a Slideaway™ LCD KVM switch/console. In just a matter of minutes, your new Slideaway™ LCD KVM switch/console can go from the box to the rack.

For convenience and flexibility, there are one standard and three optional rack mounting kits available:

Standard Rack Mount Kit	Depth (cm)
Short (Standard)	58 – 80
2X-040G (Long / Optional)	70-105

Easy Installation Rack Mount Kit	Depth (cm)
2X-041G (Short / Optional)	57 - 70
2X-042G (Long / Optional)	68 - 105

Specifications

Function	CL3108NX	CL3116NX
Computer Connections		
Direct	8	16
Maximum	128 (via Cascade)	256 (via Cascade)
Port Selection	OSD, Hotkey, Pushbutton	
Connectors		
KVM Ports	8 x SPHD-18 Female (Yellow)	16 x SPHD-18 Female (Yellow)
USB Port	1 x USB Type A Female	
Firmware Upgrade	1 x 3.5mm Audio Jack Female (Black)	
Power	1 x 3-prong AC Socket	
Switches		
Reset	1 x Semi-recessed Pushbutton	
Power	1 x Rocker	
Firmware Upgrade	1 x Slide	
LCD Control	4 x Pushbutton	
LCD On/Off	1 x Pushbutton	
Ports	8 x Pushbutton	16 x Pushbutton
LEDs		
Online	8 (Orange)	16 (Orange)
Selected	8 (Green)	16 (Green)
Power	1 x KVM Console (Dark Green) 1 x LCD (Orange)	
Lock	1 x Num Lock (Green) 1 x Caps Lock (Green) 1 x Scroll Lock (Green)	
Emulation		
Keyboard / Mouse	PS/2, USB	
Video		
Input Video Resolution	1920 x 1200 @ 60 Hz	
Panel Spec		
LCD Module	18.5" TFT-LCD	
Resolution	1366 x 768 @ 60 Hz	
Response time	5 ms	
Viewing Angle	170° (H), 160° (V)	
Pixel Pitch	0.3 mm x 0.3 mm	
Support Color	16.7M colors	
Contrast Ratio	1000 : 1	
Luminance	250 cd/m ²	
Scan Interval	1-255 seconds	
Maximum Input Power Rating	AC 100-240V; 50 - 60 Hz; 1A	
Power Consumption	AC 110V:14.1W:70BTU AC 220V:14.9W:74BTU	
Environmental		
Operating Temperature	0 - 40°C	
Storage Temperature	-20 - 60°C	
Humidity	0 - 80% RH, Non-condensing	
Physical Properties		
Housing	Metal + Plastic	
Weight	10.5 kg	10.6 kg
Dimensions (L x W x H)	48.06 x 63.17 x 4.28 cm	48.06 x 63.17 x 4.28 cm
Body Dimensions (L x W x H)	44.92 x 58.4 x 4.28 cm	44.92 x 58.4 x 4.28 cm

Note:

- For some rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.
- Body Dimensions exclude I/O ports, handles, and mounting brackets.

Product information is subject to change without prior notice.

ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
 www.aten.com E-mail: marketing@aten.com

Publish Date: 08/2019 V1.0



© Copyright 2019 ATEN® International Co., Ltd.
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their respective owners.